

Non Slip Heat Shrink Tube

A-2(NS)

Shrink ratio 2:1



Feature:

1. Skid proof flower lined, fast shrinkage, and stable performance.
2. Shrinking temperature: Start at 70°C, and full recovery at 110°C
3. Operating temperature:-55°C~105°C
4. Non slip feature for handles and fishing tackles, etc.

Dimension

Size(mm)	As supplied(mm)		After recovery(mm)		Standard package (M/pcs)
	ID	Wall thickness	Max I.D.	Average. W.T.	
φ15	≥15	0.45±0.15	8	0.85±0.15	1.0
φ20	≥20	0.50±0.15	11	0.90±0.15	0.8/1.0/1.6
φ22	≥22	0.50±0.15	12.5	0.90±0.15	0.8/1.0/1.6
φ25	≥25	0.50±0.15	14.5	1.00±0.15	0.8/1.0/1.6
φ28	≥28	0.50±0.15	15.5	1.00±0.15	0.8/1.0/1.6
φ30	≥30	0.60±0.15	17.5	1.20±0.15	0.8/1.0/1.6
φ35	≥35	0.60±0.15	20.0	1.20±0.15	0.8/1.0/1.6
φ40	≥40	0.60±0.15	23.0	1.20±0.15	0.8/1.0/1.6
φ45	≥45	0.65±0.15	25.0	1.25±0.15	0.8/1.0/1.6
φ50	≥50	0.65±0.15	28.0	1.25±0.15	0.8/1.0/1.6